

PRODUCT INFORMATION

KREP UV PLAVI MSK 6085

DESCRIPTION

Masking tape UV and weather resistant.

PRODUCT DATA

Backing	74 g/m ² UV resistant waterproof saturated paper; blue
Adhesive	Acrylic water based

	Unit	Value	Method
Total thickness	mm	0.130	PSTC 133
Adhesion to steel	N/25mm	3.75	PSTC 101
Tensile strength MD	N/25mm	100	PSTC 131
Elongation at break	%	8	PSTC 131
Temp. Resistance	°C	n.a.	=

APPLICATION

Blue masking tape recommended for light outdoor applications and also internal applications where surfaces are exposed to UV rays and moisture. Recommended to remove within 7 days.

Features	Benefits	
Acrylic water based adhesive	Good adhesion level Easy removal without adhesive residue up to 7 days	UV and weather resistant Easy unwinding
Water resistant saturated paper backing	Water resistant Well adaptable to most shaped surfaces	Compatible with most common paints Removable without breaking Hand tearable

CONDITIONS OF USE AND CONFORMITY

Product shelf life and storage: 12 months; suggested storage temperature shall range from 15°C to 25°C with max. relative humidity of 65%. Material shall be stored away from heat sources and possibly kept in original package, avoiding light exposure as well. When temperature are lower than suggested, it is always required to recondition the tape at normal temperature before use. This information is given to the best of Fost's knowledge. Values are typical and do not constitute a specification. Customers are required to do their own testing under their working condition for their intended application. Any liability arising in respect of our products will be limited to the value of those products charged to the customer excluding any consequential loss.