

## PRODUCT INFORMATION

### EUROCEL 713 TNT

#### DESCRIPTION

Double sided adhesive tape.

#### PRODUCT DATA

<b>Backing</b>	Non woven
<b>Adhesive</b>	Acrylic water based
<b>Liner</b>	Double sided siliconized paper; white

	Unit	Value	Method
<b>Total thickness (without Liner)</b>	mm	0.110	PSTC 133
<b>Adhesion to steel</b>	N/25mm	Int: 9.25 – Ext: 9.25	PSTC 101
<b>Tensile strength MD</b>	N/25mm	25	PSTC 131
<b>Elongation at break</b>	%	5	PSTC 131
<b>Temp. Resistance</b>	°C	100°C (short period)	=

#### APPLICATION

Double sided tape suitable for particular applications when good temperature resistance is required; recommended for lamination in leather goods field.

Features	Benefits	
Acrylic water based adhesive	Good adhesion level both sides Excellent resistance to ageing and UV	Plasticizer resistant Good resistance to temperature
No woven	Very adaptable also on uneven surfaces	Easy tearable

#### CONDITIONS OF USE AND CONFORMITY

Product shelf life and storage: 12 months; suggested storage temperature shall range from 15°C to 25°C with max. relative humidity of 65%. Material shall be stored away from heat sources and possibly kept in original package, avoiding light exposure as well. When temperature are lower than suggested, it is always required to recondition the tape at normal temperature before use. This information is given to the best of Sica's knowledge. Values are typical and do not constitute a specification. Customers are required to do their own testing under their working condition for their intended application. Any liability arising in respect of our products will be limited to the value of those products charged to the customer excluding any consequential loss.