

PRODUCT INFORMATION

ECOPACK 15

DESCRIPTION

Paper carton sealing tape for packaging.

PRODUCT DATA

Backing	58 g/m ² saturated crepe paper; brown or white
Adhesive	natural rubber and resins based

	Unit	Value	Method
Total thickness	mm	0.120	PSTC 133
Adhesion to steel	N/25mm	3.3	PSTC 101
Tensile strength MD	N/25mm	85	PSTC 131
Elongation at break	%	7	PSTC 131
Temp. Resistance	°C	60°C	=

APPLICATION

Paper carton sealing tape for standard packaging. Printable (not in negative) or available printed up to 3 colours (30% max printable surface). Tape must be applied at room temperature.

Features	Benefits	
Natural rubber and resins based adhesive	Good adhesion even on different types of cardboard	Good adhesion even if stored in cold temperature after closing
Saturated paper backing	Resistant to box shock Hand tearable	Identifies pilferage (as damaged cartons would be recognized if resealing were attempted)

CONDITIONS OF USE AND CONFORMITY

Product shelf life and storage: 12 months; suggested storage temperature shall range from 15°C to 25°C with max. relative humidity of 65%. Printed rolls with length more than 50 meters: 3months of shelf life. Material shall be stored away from heat sources and possibly kept in original package, avoiding light exposure as well. When temperatures are lower than suggested, it is always required to recondition the tape at normal temperature before use. This information is given to the best of Fost's knowledge. Values are typical and do not constitute a specification. Customers are required to do their own testing under their working condition for their intended application. Any liability arising in respect of our products will be limited to the value of those products charged to the customer excluding any consequential loss.